# RAISING THE STANDARDS OF LIFE SCIENCES INDUSTRIES



TP



## GERFLOR, PARTNER OF THE LIFE SCIENCES INDUSTRIES FOR 80 YEARS



## Biotech IGBMC







"Gerflor offered a full set of products and services with technical solutions for every corner of our laboratories. Furthermore we enjoyed the support of a technical team from the starting point till the end of the project." Nicolas Bensel, Technical manager

## Pharmaceuticals UPSA SITE / BRISTOL-MYERS SQUIBB







"With GTI CleanTech, SPM Decoclean and Clean Corner System, Gerflor supplies a full wall-to-floor retrofit system that became our standard to save time and money on the whole lifespan of our facility."

Denis PLEDRAN, Maintenance technician

## Research LABORATORY





## 

----- GMP CLEANROOMS

Gérard JOUVENT, Cleanroom builder

## **GERFLOR EXPERTISE**

## The specifics of the life sciences industry

### **STANDARDS**

To guarantee production guality, manufacturers in the life sciences industry (pharmaceuticals, cosmetics, etc.) need to comply with various standards and regulations, and to Good Manufacturing Practices (GMP):

- ISO 14644-1 Classification of air cleanliness
- ISO 14644-8 Control of molecular contamination
- ISO 14698-1 Control of biocontamination

To comply with them, manufacturers must use special facilities to control the production environment: cleanroom.

The constraints can vary depending on the activity and are classified as follows:

- CLASS A, B, C or D for industries subject to GMP
- ISO 4, 5, 6, 7, 8, 9 for the rest (formerly class 10, 100, 1000...)



## Gerflor solutions satisfy all the requirements of an industrial environment

differentials.



of the installation.

covings,

- hot-welding,
- easy-fit corners,

of the product

- ease of maintenance.



• GERFLOR solutions are particularly wear-resistant and withstand impacts from carts and other tanks in pharmaceutical production units. • The quality of the factory-made products -- using a tightly controlled production process -- does not depend on operating conditions nor on the installer's competence.

The formulations of GERFLOR products limit the emission of controlled particles and molecules when subject to temperature

Compacting reduces the microroughness of surfaces to limit the adhesion of particles and microorganisms.

• GERFLOR products are smooth, rot-proof, non-absorbent, watertight

• Heat-welded smooth seams to avoid any level difference (floor-floor, floor-wall...) Weld and surface-integrity controls ensure the quality

### WATERTIGHTNESS

Exclusive installation solutions ensure a perfect seal across the entire surface of the fitted zone:

• control of welding and surface integrity

### EASE OF CLEANING AND DECONTAMINATION

Factory-applied surface treatments: • does away with the need to apply acrylic emulsion for the lifetime • offer high resistance to decontamination products (hydrogen peroxide, peracetic acid, etc). • And, combined with GERFLOR installation, enable a great

## A GLOBAL SOLUTION FOR EACH AREA OF YOUR INDUSTRY

## PRIMARY PACKAGING

Mipolam BioControl Performance SPM Decoclean Clean Corner System

## PREPARATION

🖆 GTI EL5 CleanTech

CHANGING ROOM

Mural Ultra

### SECONDARY PACKAGING

GTI Max CleanTech SPM Decochoc Clean Corner System



WASHING FACILITIES

🗂 Tarasafe

SPM Decoclean Clean Corner System

LABORATORY


🖆 Mural Ultra

Mipolam BioControl

Clean Corner System


☑ Taralay Impression☑ SPM Decowood








## **CERTIFIED FLOORING FOR NEW-BUILT**



# MIPOLAM BIOCONTROL



### TOP-OF-THE-RANGE CLEANROOM FLOOR COVERING

### (ISO3) IMPACT ON PRODUCTION ENVIRONMENTS

 Particulate cleanliness: ISO3 from the standard ISO 14644-1 Electrostatic cleanliness:

Insulating and antistatic floors in accordance with EN 1081 and EN 1815

### **RESISTANCE TO COMMON DAMAGE IN CLEANROOMS**

 Resitance to microbiological damage: bacteriostatic Resistance to chemical damage: more than 100 products tested • Resistance to heavy loads: up to 5MPa i.e 500T/m<sup>2</sup>

### **CLEANING & DECONTAMINATION**

 Particulate cleanability ACS of 98.6% Microbiological cleanability GMP Class A (tested with A.Niger and E. Coli) Resistance to bio-decontamination processes


Compatible with regard to liquid and vaporised hydrogen peroxide

## CLEAN CORNER SYSTEM

• Corner system for contamination control in cleanrooms




## **CERTIFIED FLOORING FOR RENOVATION**



## WALL PROTECTION





**GERFLOR INTERNATIONAL** (Other countries) Tel: +33 (0)4 74 05 40 00 - Fax: +33 (0)4 74 05 03 13 e-mail: industry@gerflor.com **ASIA:** Gerflor Asia Tel: +852 9222 6355 - Fax: +852 3006 1449 e-mail: gerflorasia@gerflor.com AUSTRALIA/NEW ZEALAND: Gerflor Australasia Pty. Ltd Australia Tel: 1 800 060 785 - New Zealand Tel: 0 800 630 119 e-mail: gerflor@gerflor.com.au AUSTRIA/SWITZERLAND: Gerflor GmbH Tel: +43 (0)72 29/70 800-0 - Fax: +43 (0)72 29/70 800-218 e-mail: austria@gerflor.com - switzerland@gerflor.com BELGIUM/LUXEMBURG: Gerflor Benelux Tel: +32 (0)3 766 42 82 - Fax: +32 (0)3 766 29 14 e-mail: gerflorbefdgerflor.com CANADA: Gerflor International Tel: +1 438 333 0752 - Fax: +1 438 380 5425 e-mail: gerflorcanada@gerflor.com CHINA: Gerflor floorings (China) Co. Ltd. Tel: +86 21 6357 8818 - Fax: +86 21 6357 8998 e-mail: gerflorchina@gerflor.com FINLAND: Gerflor Ov Tel: +358 (0) 10 6 17 5150 - Fax: +358 (0) 10 617 5152 e-mail: info@gerflor.fi **FRANCE:** Gerflor - Service Express: (NYAcum 0 810 569 569) (NYAcum FAX) 0 810 569 570) e-mail: contactfrance@gerflor.com - industry@gerflor.com GERMANY: Gerflor Mipolam GmbH Kunden-Service Tel: +49 (0) 22 41-25 30-136 - Fax: +49 (0) 22 41-25 30-100 e-mail: kundenservice@gerflor.com IRELAND: Gerflor Ltd Tel: +353 (0) 42 966 1431 - Fax: +353 (0) 42 966 1759 e-mail: gerflorirl@gerflor.com ITALY: Gerflor S.p.A. Tel: +39 02 90 40 10 - Fax: +39 02 90 42 74 84 e-mail: gerfloritalia@gerflor.com LATIN AMERICA (Brazil): Gerflor América Latina Tel: +55 11 38 48 20 20 e-mail: gerflor@gerflor.com.br MIDDLE EAST: Gerflor Middle East Tel: +966 13 847 1779 - Fax: +966 13 847 1781 e-mail: info@gerflorme.com NETHERLANDS: Gerflor Benelux Tel: +31 (0)40 266 17 00 - Fax: +31 (0)40 257 46 89 e-mail: gerflornl@gerflor.com POLAND: Gerflor Polska Sp z o.o Tel: + 48 61 823 34 01 - Fax: + 48 61 823 34 33 e-mail: info@gerflor.pl PORTUGAL: Gerflor Iberia, SA Tel: +351 21 843 95 49 - Fax: +351 21 846 55 44 e-mail: gerflorportugal@gerflor.com RUSSIA: Gerflor zao Tel./Fax: + 7 495 785 23 71 e-mail: gerflorrussia@gerflor.ru SCANDINAVIA: Gerflor Scandinavia a.s Tel: + 47 64 95 60 70 - Fax: + 47 64 95 60 80 e-mail: gerflorscand@gerflor.no SPAIN: Gerflor Iberia, SA Tel: +34 91 653 50 11 - Fax: +34 91 653 25 85 e-mail: gerfloriberia@gerflor.com UNITED KINGDOM: Gerflor Ltd Sample service: contractuk@gerflor.com Office Tel: + 44 (0) 1926 622 600 - Fax: + 44 (0) 1926 401 647 **USA:** Gerflor North America Tel: 877 GERFLOR (437 3567) - Fax: 847 394 3753 e-mail: infoldgerflorusa.com

### GERFLOR, ECO-RESPONSIBLE SOLUTIONS



COMPOSITION 100% REACH compliant FREE of formaldehvde FREE of heavy metals FRFF of solvent



RECYCLED CONTENT 25% average recycled content 100% REACH compliant recycled content



product



RECYCLABILITY 100% recyclable



INDOOR **AIR QUALITY** TVOC emissions betwe 10 and 100 times better than norms requirements Floorscore certified No formaldehyde emission



INSTALLATION

Innovative adhesive

free installation systems



**LCA** Eco-designed according to a product specific Life Cycle Analysis - Product specific EPD (Environmental Products Declaration) available - Manufactured in an Iso 14001 and Iso 50001 certified site

- Contribution to many Green Building Schemes (LEED, HQE, BREEAM...)

WELLNESS Health: Antibacterial activity (inhibits growth > 99%) Safety: Anti slip performance Comfort: Walking comfort and impact noise reduction

### industrybygerflor.com industry@gerflor.com

### ARCHITECTURE DECORATION SPORT **TECHNOSPECIFIC**

## Gerflor. Be CONNECTED! ∎fy%æ

Follow us on LinkedIn







