

Nous avons testé nos produits à la résistance à l'impact selon la norme ASTM F 476-84 Reapproved 2002 (Standard Test Methods for Security of Swinging Door Assemblies). Les résultats de l'essai sont présentés dans le tableau ci-dessous :

*We tested our product range according to the ASTM F 476-84 Reapproved 2002 (Standard Test Methods for Security of Swinging Door Assemblies). Test results are summarized in the following table:*

Gamme de produit <i>Product range</i>	Produit testé <i>Tested product</i>	Résultat <i>Result</i>	Correspond à l'impact d'un lit d'hôpital <i>Equivalent to hospital bed impact</i>
Panneaux de protection <i>Protection and covering panels</i>	DECOCHOC	>300J	>864 kg at 3 km/h
	DECOSMIC	>300J	>864 kg at 3 km/h
	DECOWOOD	>300J	>864 kg at 3 km/h
	DECOTREND	>300J	>864 kg at 3 km/h
	DECOCLEAN	>300J	>864 kg at 3 km/h
	DECOCHOC H <sub>2</sub> O	>300J	>864 kg at 3 km/h
	DECOWOOD H <sub>2</sub> O	>300J	>864 kg at 3 km/h
	DECOTREND H <sub>2</sub> O	>300J	>864 kg at 3 km/h
Pare-Chocs et plaques de protections <i>Protection rails and plates</i>	LINEA'PUNCH NEO	>110J	>320 kg at 3 km/h
	IMPACT 200 / 120 / 60	>110J	>320 kg at 3 km/h
	CONTACT 350 / 200	>110J	>320 kg at 3 km/h
Cornières <i>Corner protection</i>	CORNEA	>110J	>320 kg at 3 km/h
	CORNEAFLEX	>110J	>320 kg at 3 km/h
	LINEA'FLEX	>110J	>320 kg at 3 km/h
	PROTECTA 2	>110J	>320 kg at 3 km/h
	PROFILA	>110J	>320 kg at 3 km/h

## PROTECTIONS MURALES ET MAINS COURANTES

[www.spm.fr](http://www.spm.fr)

**SPM international S.A.S.**  
16 rue Isabelle Eberhardt - CS 92083  
31019 Toulouse Cedex 2 - France

Tél. : +33 (0)5 34 39 40 40  
Fax : +33 (0)5 34 39 40 50  
service.clientele@spm.fr

S.A.S. AU CAPITAL DE 2 718 726.99 €  
N° SIRET 419 396 965 00040 – APE 4673B  
R.C.S. 419 396 965 TOULOUSE  
TVA intracommunautaire - FR 27 419 396 965

Gamme de produit <i>Product range</i>	Produit testé <i>Tested product</i>	Résultat <i>Result</i>	Correspond à l'impact d'un lit d'hôpital <i>Equivalent to hospital bed impact</i>
Mains courantes pare-chocs <i>Protection handrails</i>	ESCORT'DUO	>110J	>320 kg at 3 km/h
	LINEA'DUO	>110J	>320 kg at 3 km/h
	PERFORMER 2	>110J	>320 kg at 3 km/h
	STARLINE GAINÉE PVC <i>PVC SHEATHED</i>	>110J	>320 kg at 3 km/h
	STARLINE ANODISÉE <i>ANODISED</i>	>110J	>320 kg at 3 km/h
	LINEA'TOUCH + GAINÉE PVC <i>PVC SHEATHED</i>	>110J	>320 kg at 3 km/h
Mains courantes tubulaires <i>Tubular handrails</i>	LINEA'TOUCH GAINÉE PVC <i>PVC SHEATHED</i>	>60J	>173 kg at 3 km/h
	LINEA'TOUCH DECOWOOD	>60J	>173 kg at 3 km/h
	LINEA'TOUCH ANODISÉE <i>ANODISED</i>	>60J	>173 kg at 3 km/h
	ESCORT GAINÉE PVC <i>PVC SHEATHED</i>	>60J	>173 kg at 3 km/h
	ESCORT DECOWOOD	>60J	>173 kg at 3 km/h
	ESCORT ANODISÉE <i>ANODISED</i>	>60J	>173 kg at 3 km/h

## PROTECTIONS MURALES ET MAINS COURANTES

[www.spm.fr](http://www.spm.fr)

SPM international S.A.S.  
16 rue Isabelle Eberhardt - CS 92083  
31019 Toulouse Cedex 2 - France

Tél. : +33 (0)5 34 39 40 40  
Fax : +33 (0)5 34 39 40 50  
service.clientele@spm.fr

S.A.S. AU CAPITAL DE 2 718 726.99 €  
N° SIRET 419 396 965 00040 – APE 4673B  
R.C.S. 419 396 965 TOULOUSE  
TVA intracommunautaire - FR 27 419 396 965