

# MIPOLAM CLASSIC


gerflor.com



*The Original*  
MIPOLAM 1937

**Gerflor**<sup>®</sup>  
the flooring group

# MIPOLAM CLASSIC



**0125 Truffle**  
NCS: 6005-Y50R / LRV: 17.5



**0124 Tortora**  
NCS: 3010-Y20R / LRV: 36.9



**0014 Brown**  
NCS: 3010-Y40R / LRV: 39.2



**0123 Corallo**  
NCS: 2060-Y80R / LRV: 21.2



**0013 Pewter**  
NCS: 6502-B / LRV: 18.2



**0005 Steel** ▲  
NCS: 3502-B / LRV: 38.3



**0301 Beige**  
NCS: 1505-Y30R / NCS: 65.5



**0003 Ivory** ▲  
NCS: 2010-Y30R / LRV: 56.1



**0006 Honey**  
NCS: 2020-Y30R / LRV: 46.0



**0108 Pepper**  
NCS: 2500-N / LRV: 49.1



**0303 Grey**  
NCS: 3005-B20G / LRV: 42.2



**0002 Platinum** ▲  
NCS: 2002-B / LRV: 56.1







**0127 Bermuda**  
NCS: 5030-B10G / LRV: 13.4



**0126 Nordica**  
NCS: 2040-B / LRV: 34.2



**0010 Azure**  
NCS: 3030-B / LRV: 32.6



**0120 Borneo**  
NCS: 4020-G40Y / LRV: 27.5



**0122 Pineapple**  
NCS: 1050-Y20R / LRV: 51.8



**0121 Green Leaf**  
NCS: 2040-G60Y / LRV: 41.1

## MIPOLAM CLASSIC



**Directional design**



**Medium to heavy traffic resistance**



**Flexible flooring, easy to install & weld**



**Ease of maintenance**



**Roll 2 x 20lm - Tiles 608x608 mm**



**Recycled content 25%  
100% Recyclable**



**Indoor air quality: TVOC 100 times below standard**



**WE CARE | WE ACT.**

Our Commitments for a Sustainable future



Z0013079

Mipolam Classic  
1.5 mm

Mipolam Classic  
2 mm

## DESCRIPTION

Total Thickness	EN ISO 24346	mm	1.5	2.0
Weight	EN ISO 23997	g/sq.m	2520	3300
Width/Length of Sheet	EN ISO 24341	cm/lm	200/20	200/20
Tile size	EN ISO 24342	mm	-	300 x 300* / 608 x 608
Number of tiles per package	-	-	-	50 / 20

## CLASSIFICATION

Norm/Product Specification	-	-	EN ISO 10581	EN ISO 10581
European classification	EN ISO 10874	class	23-31	34-43
Fire Rating	EN 13 501-1	class	Bfl-s1	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2	< 2






## PERFORMANCE

Type Binder content	EN ISO 10581	type	II	II
Dimensional stability	EN ISO 23999	%	≤ 0.40	sheet ≤ 0.40 tile ≤ 0.25
Impact sound insulation	EN ISO 717-2	dB	-	4
Residual indentation	EN ISO 24343-1	mm	≈ 0.03	≈ 0.03
Castor Chair test (type W)	ISO 4918	-	OK	OK
Thermal Conductivity	EN ISO 10456	W/[m.K]	0.25	0.25
Colour Fastness	EN 20 105-B02	degree	≥ 6	≥ 6
Surface Treatment	-	-	PUR	PUR
Chemical Products fastness	EN ISO 26987	class	OK	OK

## ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10	< 10
--------------------	-------------	--------------------	------	------

## CE MARKING

CE	EN 14041	-			
					

\* upon special request

Product description and technical data sheet available in various languages. See our Gerflor Country websites.

Installation and Maintenance Guidelines, Complementary ranges available on our Gerflor website.



Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

**IMPORTANT:** The information contained in this document is valid from 01/09/2021 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

## WE CARE | WE ACT. Our Commitments for a Sustainable future



**CARBON FOOTPRINT\***

-20 % kg CO<sub>2</sub> equivalent/m<sup>2</sup> between 2020 and 2025



**BIOSOURCED CONTENT\*\***

10 % by 2025



**RECYCLED CONTENT**

30 % by 2025



**ADHESIVE FREE\*\***

35 % by 2025



**ANNUAL VOLUME RECYCLED**

60 000 t by 2025

\* Scopes 1 and 2 defined in the GHG protocol \*\*\* % of activity with biosourced materials \*\* % of activity - adhesive free solution

**Gerflor**  
theflooringgroup