

### DESCRIPTION

Total Thickness	EN ISO24346 (EN 428)	mm	0.93
Weight	EN ISO 23997 (EN 430)	g/m <sup>2</sup>	200
Width	EN ISO 24341 (EN 426)	cm	100
Length	EN ISO 24341 (EN 426)	m	15
Packaging content		m <sup>2</sup>	15
Packaging Weight		kg	3
Article code			17980001

### CLASSIFICATION

Fire rating	EN 13501-1	classe	Efl (underlayer alone) Bfl-s1 (with homologated floors)
-------------	------------	--------	--

### PERFORMANCE

Impact sound insulation	EN ISO 717-2	dB	16 (with Creation 70 Clic) 15 (with other homologated floors)
Thermal resistance	EN 12664	m <sup>2</sup> K/W	0.023
Compressive Strength	EN ISO 3386 / EN826	kPa	400
Compressive Strength	EN ISO 3386 / EN826	t/m <sup>2</sup>	40



This underlay is recommended by Gerflor for the following products :

- CREATION 70 CLIC
- CREATION 55 CLIC
- CREATION 55 SOLID CLIC
- CREATION 30 CLIC
- CREATION 30 SOLID CLIC
- VIRTUO 55 CLIC
- VIRTUO 30 CLIC
- SENSO PREMIUM CLIC 2
- SENSO 20 LOCK (For classe 22 use only)
- RIGID 30 LOCK (For classe 22 use only)

It is not suitable for industrial or semi-industrial application