

RECREATION 60 is a 6 mm sport flooring, heterogeneous calendered roll, embossed, available in 1.5m wide sheet with a length up to 26,5 m.

The product comprises a UV cured polyurethane surface treatment PUR PROTECT ensuring easy maintenance and the right balance between slide and grip. It has a closed cell foam backing and a 100% pur PVC surface complex, reinforced with a fiber-glass grid for a better dimensional stability and a better indentation resistance ( $\leq 0,5$  mm according to EN1516). It is composed of inlaid colours or of printed designs encapsulated by a transparent wear layer.

Its sports characteristics allow him to reach a shock absorption (EN14808)  $\geq 28$  % with a P2 ranking. The vertical deformation following EN 14809 is  $\leq 0.8$  mm and the slippery resistance following EN 13036-4 stays between 80 and 110. Abrasion resistance following EN 1517 is  $\leq 350$  mg. This product allows a 18 dB sound insulation. Its construction allows him a ball rebound  $\geq 98\%$ .

According to ISO 21702, RECREATION 60 shows anti-viral activity against Human Coronaviruses : it reduces the number of virus by 99,37% after 2h00.

According to ISO 22196, it has anti-bacterial activity against E. coli, S. aureus and MRSA of 99% after 24h00. This product allows a Cfl-s1 fire rating.

It does not contain any heavy metals or CMR 1&2 components, it is 100% compliant with REACH. The product emission rate of volatile organic compounds is  $<100\mu\text{g}/\text{m}^3$  (TVOC after 28 days ISO 16000-6). It is 100% recyclable.

Manufacturer shall provide upon request full EN14904 test report carried out by independent and approved test laboratory, and a declaration of performance for this product.

---