RECREATION SURFACE

IDEAL FOR ROLLING SPORTS AND HEAVY LOADS SPORTS SURFACES

| DESCRIPTION | STANDARDS | REQUIREMENTS | WOOD DESIGN | SOLID COLOR |
|--|---|--------------------|--------------------------------|-----------------|
| PRODUCT DESCRIPTION | | | | |
| Wearlayer | - | - | 100% Pure Vinyl | |
| Surface Complex | - | - | - | |
| Foam Backing | - | - | - | |
| Total Thickness | - | - | 0.08" (2.1 mm) | |
| Wearlayer Thickness | - | - | 0.08" (2.1 mm) | |
| Weight | - | - | 0.59 lb/f² (2.9 kg/m²) | |
| Roll Width | - | - | 4' 11" (1.5 m) | |
| Roll Length | - | - | 86 [°] 6″ (26.4 m) | 67' 3" (20.5 m) |
| SPORT CHARACTERISTICS | | | | |
| Sport Properties | ASTM F2772 | - | - | |
| Safety | ASTM F2772 | - | - | |
| Vertical Deformation | ASTM F2772 | ≤ 3.5 mm | - | |
| Sliding Effect | ASTM F2772 | 80 - 110 | 80 - 110 | |
| Ball Rebound | ASTM F2772 | - | ≤ 96% | |
| Anti-Friction Burns | - | Class 1 | PUR Protect® | |
| ENVIRONMENT HEALTH & SAFETY | | | | |
| Ease of Maintenance | - | - | PUR Protect® / No wax for life | |
| Restriction Use of Harmful Chemicals | MRc4 LEED v4 | - | Complies with REACH | |
| Naturally Bacteriostatic: Combats MRSA, E. coli and S. aureus* | ISO 22196 | - | ОК | |
| Allergen Free | - | - | ОК | |
| Indoor Air Quality | EQc2 LEED v4 | - | FloorScore® Certified | |
| Recycled Content | MRc3 LEED v4 | - | 50% | |
| INSTALLATION METHOD | | | | |
| Full-Spread Adhesive | ASTM F21870 (F1869) | ≤ 95% RH (≤ 10 lb) | M | |
| Moisture Mitigation System | ASTM F21870 (F1869) | ≤ 92% RH (≤ 10 lb) | ISOLSPORT | |
| WARRANTY | 15-year limited warranty when installed in accordance with Gerflor's installation instructions. | | | |

*The implementation of an effective cleaning method is the best defense against infection.

samples@gerflorusa.com

877.437.3567

