



New Formats

Herringbone



Creation 55 HB

Gerflor®



BALLERINA



QUARTET & QUARTET FAUVE



BOSTONIAN OAK BEIGE



QUARTET FAUVE



TWIST

Creation 55 HB



QUARTET 0503

Dry Back 152 X 762 | RIGID AC 125 x 750



QUARTET FAUVE 0859

Dry Back 152 X 762



BALLERINA 0347

Dry Back 152 X 762 | RIGID AC 125 x 750



TWIST 0504

Dry Back 152 X 762








BOSTONIAN OAK BEIGE 0853

Dry Back 152 X 762



DESIGN SHADE VARIATION:  Light  Medium

Creation 55 HB

	Creation 55 HB Dry Back		Creation 55 Rigid Acoustic	
DESCRIPTION / BESCHREIBUNG / BESCHRIJVING / DESCRIPCIÓN / DESCRICÃO / DESCRIZIONE				
Total Thickness / Épaisseur totale / Gesamtdicke / Totale dikte / Espesor total / Espessura total / Spessore totale	EN ISO 24346	mm	2.50	6.00
	ASTM F386-02	inch	0.10	0.24
Thickness of the wearlayer / Épaisseur couche d'usure / Dicke der Nutzschrift / Dikte van de slijtlaag / Espesor capa de uso / Espessura camada de desgaste / Spessore strato di usura	EN ISO 24340	mm	0.55	0.55
	ASTM F410-02	inch	0.022	0.022
Weight / Poids / Flächengewicht / Gewicht / Peso / Peso / Peso	EN ISO 23997	g/m ²	3 850	9 480
Size / Format / Afmetingen / Dimensiones / Dimensões / Dimensione Number of planks or tiles per box / Sqm per box - Nombre de lames ou dalles par boîte / m ² par boîte - Planken-/Fliesenanzahl pro Karton / m ² pro Karton - Aantal tegels/planken per verpakking/ aantal m ² per verpakking - Numero doghe/piastre e m ² per scatola - Cantidad de losetas / Caja / Quantidade dosmosaicos / Caixa & m ²	ISO 24342 ASTM F 536	mm inch	152 x 762 mm / 33 / 3,82m ²	125 x 750 / 16 / 1.50m ²
		Number of planks / m ²		
CLASSIFICATION / CLASSIFICATION / KLASSIFIKATION / CLASSIFICATIE / CLASIFICACIONES / CLASSIFICAÇÕES / CLASSIFICAZIONI				
Norm - Product Specification / Norme - Spécification produit/Produktnorm - Technische eigenschappen / Normas - Norma prodotto	-	-	EN ISO 10582	EN ISO 10582
	ASTM F 1700-04	-	Class III Type B	Class III Type B
European Classification/Classement européen / Europäische Klassifizierung / Europese classificatie / Classificación europea / Classificação Europeia / Europea	EN ISO 10874	class	33 - 42	33 - 42
Fire Rating / Classement Feu / Brandverhalten / Brand classificatie / Fuego / Fogo / Reazione al fuoco	EN 13 501-1	class	Bfl-s1	Bfl-s1
Static Electrical Propensity / Potentiel de charge / Begehaufladung / Elektrische eigenschappen / Comportamiento electrostático / Comportamento electrostático / Resistenza elettrica	EN 1815	kV	< 2	< 2
Slip Resistance Wet / Glissance humide / Rutschhemmung / Anti-slip / Deslizamiento húmedo / Escorregamento húmido / Scivolosità umida ¹⁾	DIN 51130 / BGR 181	class	R10	R10
PERFORMANCES / TECHNISCHE EIGENSCHAFTEN / TESTRESULTAAT / PERFORMANCE / CUALIDADES TÉCNICAS / CARATTERISTICHE TECNICHE				
Wear Resistance / Résistance à l'usure / Verschleißverhalten / Slijtvastheid / Abrasión / Abrasão / Resistenza all'abrasione	EN 660.2	mm ³	< 2.0	< 2.0
Wear Group / Groupe d'abrasion / Verschleißgruppe / Groep slijtvastheid / Grupo de abrasión / Grupo de abrasão / Gruppo di abrasione	QB 30	group	T	T
Type Binder content / Teneur en agent liant / Bindemittelgehalt / Contenido en ligante / Conteúdo em ligante en agent	ISO 10582	group	I	I
Dimensional stability (norm) / Stabilité dimensionnelle (norme) / Maßstabilität (norm) / Maatvastheid (norm) / Estabilidad Dimensional (Exigencia) / Estabilidade dimensional (normalização) / Stabilità dimensionale (requisito normativo)	EN ISO 23999	%	< 0.25	< 0.15
Dimensional stability (average measured value) / Stabilité dimensionnelle (valeur moyenne mesurée) / Maßstabilität (Durchschnittswert) / Maatvastheid (gemeten gemiddelde waarde) / Estabilidad Dimensional (Valor medido) / Estabilidade Dimensional (Valor medio) / Stabilità dimensionale (rilevata)	-	%	< 0.10	< 0.10
Residual Indentation / Poinçonnement statique rémanent / Resteindruck / Indrukbelasting / Punzonamiento / Punçoamento / Impronta	EN ISO 24343-1	mm	< 0.10	< 0.05
Impact sound insulation / Isolation acoustique bruits de chocs / Trittschallverbesserungsmaß / Geluidsisolatie / Acústica / Isolamento acústico	EN ISO 717-2	dB	4	19
Room Impact / Sonorité à la marche / Raumschall / Loopgeluid / Rumore al calpestio / Sonoridad en la pisada / Sonoridade ao andar	NFS 31074	dB	77	81
Castor chair test / Essai de la chaise à roulettes / Stuhlrollenbeanspruchung / Rolweerstand bureaustoelen / Determinación del efecto de una silla con ruedas / Resistência a cadeiras de rodas / Resistenza al passaggio di sed	ISO 4918	-	OK	OK
Thermal Conductivity / Conductivité thermique / Wärmeleitfähigkeit / Thermische weerstand / Conductividad térmica / Contutividade térmica / Resistenza termica / Värmeledningsmotstånd / Varmemotstånd	EN ISO 10456	W/(m.K)	0.25	0.25
Colour Fastness / Solidité lumière / Lichtechtheit / Lichtechtheid / Resistencia a la luz / Estabilidade das cores / Solidità alla luce	EN ISO 105 - B02	Degree	> 6	> 6
Surface Treatment / Traitement de surface / Oberflächenvergrüung / Oppervlaktebehandling / Tratamiento de superficie / Tratamento de superficie / Trattamento di superficie	-	-	ProtecShield™	ProtecShield™
Chemical Products Resistance / Résistance aux produits chimiques / Verhalten gegenüber Chemikalien [2] / Chemische bestendigheid / Resistencia a los productos químicos / Resistência aos produtos químicos / Resistenza ai prodotti chimici	EN ISO 26987	-	OK	OK
ENVIRONMENT/INDOOR AIR QUALITY / QUALITE DE L'AIR INTERIEUR / UMWELT/RAUMLUFTQUALITÄT / AMBIENTE/QUALIDADE DO AR INTERIORENVIRONNEMENT/ MEDIO AMBIENTE/CALIDAD INTERIOR DEL AIRE INTERIOR / MEIOAMBIENTE/QUALIDADE DO AR INTERIOR				
TVOC after 28 days / TVOC après 28 jours / TVOC (28 Tage) / TVOC (28 dagen) / TVOC (28 dias) / TVOC (28 dias) / TVOC (28 giorni) / TVOC (28 dagar) / TVOC (28 dager)	ISO 16000-6	µ/m ³	< 10	< 10
Certification / Zeugnis / Certificado / Certificação	-	-	Floorscore®	Floorscore®
CE MARKING / MARQUAGE CE / CE KENNZEICHNUNG / EG_CONFORMITEITSMERK / MARCA DE CONFORMIDAD CE / MARCA DE CONFORMIDADE CE / MARCATURA CE DI CONFORMITA				
	EN 14041	-	   	

[1] Plan incliné avec huile / Ramp test with oil / Schiefe Ebene

[2] Beständig gegenüber nicht färbenden alkoholhaltigen Handdesinfektionsmitteln, Haushaltschemikalien und verdünnten Säuren und Laugen bei kurzzeitiger Einwirkung.

IMPORTANT: The information contained in this document is valid from 01/11/2022 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

We care / We act Our Commitments for a Sustainable future


CARBON FOOTPRINT*
-20 % kg
CO₂ equivalent/m²
between 2020 and 2025


BIOSOURCED CONTENT**
10 % by 2025


RECYCLED CONTENT
30 % by 2025


ADHESIVE FREE***
35 % by 2025


ANNUAL VOLUME RECYCLED
60 000 t by 2025

Gerflor®

* Scopes 1 and 2 defined in the GHG protocol ** % of activity with biosourced materials *** % of activity - adhesive free solution