



	PRODUCT CHARACTERISTICS			
	Standard	Requirements	Unit	Results
	<b>FULL SYSTEM DESCRIPTION</b>			
Dimensions panels			lm x lm	1,235 x 0,46 (thickness: 18,8 mm)
Dimensions absorbing foams			lm x lm	2,0 x 1,6 (thickness :15 mm)
Total thickness of the system	EN ISO 24346	-	mm	36
Total weight of the system	EN ISO 23997	-	kg/m <sup>2</sup>	21
	<b>TOP FLOORING "Taraflex Surface" DESCRIPTION</b>			
Surface treatment	-	-	-	Triple-Action ProtecSol
Surface complex	-	-	-	D-Max
Thickness	EN ISO 24346	-	mm	2
Weight	EN ISO 23997	-	kg/m <sup>2</sup>	2.9
Length	EN ISO 24341	-	lm	26.5 max
Width	EN ISO 24341	-	lm	1.5
	<b>SPORT PROPERTIES</b>			
Shock absorption	EN 14808	≥ 40	%	A3
Vertical Deformation	EN 14809	≤ 3,5	mm	≥ 1,8 to < 3,5
Sliding Coefficient	EN 13036-4	80 - 110	-	80 - 110
Ball Bounce	EN 12235	≥ 90	%	≥ 90
	<b>TECHNICAL CHARACTERISTICS</b>			
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	≥ 8
Rolling Load resistance	EN 1569	≤ 0,5	mm	≤ 0,5
Indentation resistance	EN 1516	≤ 0,5	mm	≤ 0,5
	<b>CLASSIFICATION</b>			
Fire	EN 13501-1	-	-	
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1)	ISO 22196			> 99 % inhibits growth
	<b>DECLARATION OF PERFORMANCE</b>			
		-		Fire Shock Absorption Sliding Coefficient Abrasion Resistance Rolling Load Resistance

(1) The implementation of an effective cleaning method is the best defence against infection