AWTA Product Testing

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client: Gerflor Australasia Pty Ltd

17 Cato Street

Hawthorn East VIC 3123

17-006772 Test Number :

12/01/2018

Print Date 12/01/2018

Issue Date

"Mipolam Affinity" **Sample Description** Clients Ref:

Width

Blistering

Vinyl floorcovering

PVC Nominal Composition:

Nominal Mass per Unit Area/Density:

Nominal Thickness: 2mm 2850q/m2

AS/ISO 9239.1-2003

Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a **Radiant Heat Source**

Date of Sample Arrival 29/11/2017 **Date Tested** 11/01/2018

CHF Value 1 2 3 Mean Length 92 9.5 8.8 kW/m² Width 9.2 kW/m² 2 Smoke Value 3 Mean Length 61 42 66 %.min 56

Melting Yes

67

116419 24223 Page 1 of 2

Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Chemical Testing

Mechanical Testing

Performance & Approvals Testing

: Accreditation No

Accreditation No · Accreditation No.



%.min

Yes

A. JACKSON B.Sc.(Hons)

983

1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client: Gerflor Australasia Pty Ltd

17 Cato Street

Hawthorn East VIC 3123

Test Number : 17-006772

Issue Date

Print Date : 12/01/2018

12/01/2018

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2001 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each specimen was adhered to a substrate of 6mm thick fibre reinforced cement board using Roberts 656 adhesive and clamped prior to testing.

116419 24223 Page 2 of 2

C Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Chemical Testing - Mechanical Testing

- Performance & Approvals Testing

: Accreditation No.

: Accreditation No.

983 985 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



IICHAEL A. JACKSON B.Sc.(Hons)