

## OIL-WET INCLINING PLATFORM SLIP RESISTANCE TEST

### Taraflex Surface sheet vinyl

<b>Prepared for:</b>	Jutta Fronert Gerflor Australasia Pty Ltd 17 Cato Street HAWTHORN EAST VIC 3123
<b>Specimen Description:</b>	Taraflex Surface sheet vinyl, 497x1075 mm.
<b>No. of Specimens:</b>	1 off
<b>Surface Structure:</b>	Structured
<b>Specimen Preparation:</b>	Washed with water and pH neutral detergent, rinsed then dried.
<b>Specimen Configuration:</b>	Fixed
<b>Test Direction:</b>	Test direction not applicable.
<b>Joint Type &amp; Width:</b>	N/A
<b>Air Temperature:</b>	21°C
<b>Test Standard:</b>	AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix D - Oil Wet Inclining Platform Test
<b>Test Shoe:</b>	Leipzig V73-SP
<b>Test Location:</b>	ATTAR, Unit 1, 64 Bridge Road, Keysborough.
<b>Test Date:</b>	19 July 2018
<b>Test Personnel:</b>	Awel Guled and Dale Siegle

<b>Displacement Space</b> (rounded to the nearest 0.5cm <sup>3</sup> /dm <sup>2</sup> ):	Not tested
<b>Displacement Space Assessment Group</b> (Appendix E, AS 4586 - 2013):	Not tested
<b>Corrected mean overall acceptance angle (<math>\alpha_{ave}</math>)</b> (rounded down to the nearest degree):	<b>8°</b>
<b>Classification:</b>	<b>R9</b>

These results apply only to the specimens tested and it is recommended that before selection of flooring or paving materials the effect of service conditions, including maintenance procedures and wear on their slip resistance be checked.



Dale Siegle  
Compliance and Test Technician

Reviewed By:



Marcus Braché  
Senior Engineering Technician  
Approved Signatory

**This report may not be reproduced except in its entirety**

**Page 1 of 3**



**Figure 1:** Taraflex Surface sheet vinyl

**CLASSIFICATION CRITERIA – AS 4586 - 2013**  
**Oil Wet Inclining Platform Test – Appendix D**

**Compliance**

**TABLE 5: CLASSIFICATION OF PEDESTRIAN SURFACE MATERIALS ACCORDING TO THE OIL-WET INCLINING PLATFORM TEST**

<b>Classification</b>	<b>Angle, degrees</b>
No Classification	<6
R9	≥6 <10
R10	≥10 <19
R11	≥19 <27
R12	≥27 <35
R13	≥35