





Slip Check to AS 4586-2013 Mipolam Concept

Report Number: M1018b

Report Date: 16 December 2020

Total Number of Pages 2

Accredited for compliance with ISO/IEC 17025 - Testing

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports

Issued by

Safe Environments Pty Ltd Unit 4, 40 Bessemer Street Blacktown NSW 2148 **Prepared for**

Gerflor Australasia Pty Ltd Cato Street Hawthorn East VIC 3123 Approved by

Nasser Cura Authorised Signatory 16 December 2020

Test Report No. M1018b

Slip Resistance Classification of New Pedestrian Surface Materials

AS 4586-2013 Appendix D (Oil-Wet Inclining Platform Test)

The slip resistance classification has been determined for unused surfaces using specific conditions. Factors such as usage, cleaning systems, applied coatings and patterns of wear may affect the characteristics of the surface after classification. Standards Australia Handbook 198:2014 *Guide to the specification and testing of slip resistance of pedestrian surfaces* provides guidance for the selection of slip resistant pedestrian surfaces classified in accordance with AS 4586-2013. It is recommended that this test report be read in conjunction with AS 4586 and HB 198.

Requested by: Gerflor Australasia Pty Ltd

Client Address: Cato Street

Hawthorn East VIC 3123

Product Manufacturer: Gerflor

Product Description: Mipolam Concept

Surface Structure: Smooth
Fixed/Unfixed: Fixed
Joint Width: N/A

Test conducted according to: AS 4586-2013 Appendix D (Incorporating Amendment No. 1)

Location: 4/40 Bessemer Street, Blacktown NSW 2148

Conducted by: Oshi Barkat & Connor Murphy

Test Shoe Type: Bergmann with Leipzig V73-SP sole form

Date: 15 December 2020 Cleaning: As Received

Air Temperature: 24°C

Displacement Space: Not Measured

Displacement Space Assessment Group: NA

Corrected Mean Overall Acceptance Angle:	6°
Slip Resistance Assessment Group:	R9