


DESCRIPTION				
Total thickness	EN ISO 24346	mm	3.40	
Thickness of wearlayer	EN ISO 24340	mm	0.20	
Weight	EN ISO 23997	g/m ²	6360	
Size	EN ISO 24342	mm	177 x 1210	298 x 602
Number of planks / tiles and sqm per box	-	-	9 / 1.93 m ²	11 / 1.97 m ²
CLASSIFICATION				
Norm / Product specification	-	-	EN ISO 10582	
European classification	EN ISO 10874 (EN 685)	class	22	
Fire rating	EN 13 501-1	class	Bfl-s1	
Static electrical propensity	EN 1815	kV	< 2	
Slip resistance wet: ramp test with oil	EN 16165:2021 – Appendix B (DIN 51 130)	class	-	
PERFORMANCE				
Wear resistance	EN 660.2	mm ³	< 2.0	
Wear group	-	group	T	
Type binder content	EN ISO 10582	type	I	
Dimensional stability	EN ISO 23999	%	≤ 0.15	
Residual indentation	EN ISO 24343-1	mm	≤ 0.10	
Impact sound insulation	EN ISO 717-2	dB	3	
Room impact noise	NF S 31074	dB	78	
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	
Colour fastness	EN ISO 105 - B02	degree	≥ 6	
Surface treatment	-	-	PUR+	
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 100	
CE MARKING				
CE	EN 14041	-		
		-	