

ADVENTURER

gerflor.co.uk
gerflor.ie
gradus.com

Uniclass Pr_35_57_11_62
Cl/SfB (43) Tn6

ADVENTURER

SPECIFICATION

Product Format	Tile	Pvc Impervious
Product Dimensions	500mm x 500mm	2 metres
Product Construction	Tufted Loop Pile	Tufted Loop Pile
Surface Yarn	100% Solution Dyed Nylon	100% Solution Dyed Nylon
Total Carpet Weight	4380 g/m ²	4380 g/m ²
Tufted Pile Weight	500 g/m ²	500 g/m ²
Gauge	1/13" (51.2 per dm)	1/13" (51.2 per dm)
Stitches	36.2 per dm	36.2 per dm
Primary Backing	Non-woven	Non-woven
Secondary Backing	Bitumen	Pvc
Total Carpet Thickness	6.2mm	6.9mm

PERFORMANCE SPECIFICATION

Classification	Heavy Commercial	Heavy Commercial
Castor Chair BS EN 985 Test A	Pass	Pass
CAMRASO Method E6-1	-	Impermeable
Impact Sound Insulation EN ISO 10140-3	22dB	22dB
Static Electricity ISO 6356	<2kV	<2kV

FLAMMABILITY

BS EN 13501-1	Class Bfl-s1	Class Cfl-s1
---------------	--------------	--------------

WARRANTIES

Wear Warranty	15 Year	15 Year
Anti-static Warranty	10 Year	10 Year
Fade Warranty	5 Year	5 Year

INSTALLATION

Pvc impervious backed carpet has specific installation requirements, visit www.gerflor.co.uk for installation instructions.

ADHESIVES

For recommended adhesives contact Technical Services.



The information contained in this document is valid from 1/4/2023 and is subject to change at any time without notice.

Contact us to order free samples

UNITED KINGDOM:
Gerflor Flooring UK Ltd
Park Green, Macclesfield,
Cheshire, SK11 7LZ
Tel: 01625 428922
E-mail: contractuk@gerflor.com
Visit: www.gerflor.co.uk

IRELAND:
Gerflor Ltd
Ballybay Road, Co. Monaghan,
A81 YD83, Republic of Ireland
Tel: +353 (0) 42 966 1431
E-mail: gerflorirl@gerflor.com
Visit: www.gerflor.ie

Gerflor
the flooring group