



The Original
MIPOLAM 1937

Mipolam Classic

Gerflor®

Mipolam Classic



0125 Truffle
LRV: 17.50 / NCS : 6005-Y50R



0005 Steel
LRV: 38.30 / NCS : 3502-B



0108 Pepper
LRV: 49.10 / NCS : 2500-N



0124 Tortora
LRV: 36.90 / NCS : 3010-Y20R



0303 Grey
LRV: 42.20 / NCS : 3005-B20G



0013 Pewter
LRV: 18.20 / NCS : 6502-B



0014 Brown
LRV: 39.20 / NCS : 3010-Y40R



0002 Platinum
LRV: 56.10 / NCS : 2002-B



0003 Ivory
LRV: 56.10 / NCS : 2010-Y30R



0301 Beige
LRV: 65.50 / NCS : 1505-Y30R



0123 Corallo
LRV: 21.20 / NCS : 2060-Y80R



0010 Azure
LRV: 32.60 / NCS : 3030-B



0122 Pineapple
LRV: 51.80 / NCS : 1050-Y20R



0121 Green Leaf
LRV: 41.10 / NCS : 2040-G60Y

14 COLOURS

Directional design



Medium to heavy traffic resistance



Easy maintenance
• PUR+ surface treatment



Flexible rolls & tiles, easy to install & weld




**Recycled content 25%
100% Recyclable**



Indoor Air Quality
• TVOC 100 times below standard

we care / we act



All colours available as 300 x 300mm tiles upon request for a minimum order quantity of 500 sqm - ● Thickness: 1.5 mm - Sheet format only
LRV: Light Reflectance Value - Welding rods: please refer to gerflor.com



Mipolam Classic

Description				
Total thickness	EN ISO 24346	mm	1.50	2.00
Weight	EN ISO 23997	g/sq.m	2520	3300
Width/Length of sheet	EN ISO 24341	cm/lm	200/20	200/20
Tile Size	EN ISO 24342	mm	-	300×300 ⁽¹⁾ / 608×608
Number of tiles per package	-	-	-	50/20

Classification				
Norm/product specification	-	-	EN ISO 10581	EN ISO 10581
European classification	EN ISO 10874	class	23 - 31	34 - 43
Fire rating	EN 13501-1	class	B _{fl} -s1	B _{fl} -s1
Static electrical propensity	EN 1815	kV	< 2	< 2

Performances				
Type binder content	EN ISO 10581	type	II	II
Dimensional stability	EN ISO 23999	%	≤ 0.40	sheet ≤ 0.40 tile ≤ 0.25
Impact sound insulation	EN ISO 717-2	dB	-	4
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10	≤ 0.10
Residual indentation (average measured value)	-	mm	≈ 0.03	≈ 0.03
Castor chair test (type H)	ISO 4918	-	OK	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6	≥ 6
Surface treatment	-	-	PUR	PUR
Chemical products resistance	EN ISO 26987	class	OK	OK

Environment / Indoor Quality Air				
TVOC after 28 days	ISO 16000-6	microgram/m ³	< 10	< 10
Certification	-	-	Floorscore®	

CE marking				
	EN 14041	-		

(1) Tiles (300 × 300 mm) available for a minimum order quantity of 500 sqm.

Product description , installation & maintenance guidelines as well as complementary ranges available on Gerflor websites

 Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

IMPORTANT: The information contained in this document is valid from 01/09/2023 and is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

We care / We act Our Commitments for a Sustainable future

 CARBON FOOTPRINT* -20 % kg CO ₂ equivalent/m ² between 2020 and 2025	 BIOSOURCED CONTENT** 10 % by 2025	 RECYCLED CONTENT 30 % by 2025	 ADHESIVE FREE*** 35 % by 2025	 ANNUAL VOLUME RECYCLED 60 000 t by 2025
--	--	--	--	--



* Scopes 1 and 2 defined in the GHG protocol ** % of activity with biosourced materials *** % of activity - adhesive free solution