

## IDEAL FOR EVERYDAY PLAY

DESCRIPTION	STANDARDS	REQUIREMENTS	WOOD DESIGN	SOLID COLOR
<b>PRODUCT DESCRIPTION</b>				
Reference Specification	ASTM F1303	-	Type 1, Grade 1	Type 1, Grade 1
Surface Treatment	-	-	PUR Protect® UV Factory Applied	PUR Protect® UV Factory Applied
Foam	ASTM F1303	-	Class C: Cushion Foam Backing	Class C: Cushion Foam Backing
Total Thickness	ASTM F386	-	0.18" [4.5 mm]	0.18" [4.5 mm]
Total Wearlayer	ASTM F410	-	0.04" [1 mm]	0.04" [1 mm]
Roll Width	-	-	4' 11" [1.5 m]	
Roll Length	-	-	86' 6" [26.4 m]	67' 3" [20.5 m]
Weight	-	-	0.53 lb/ft <sup>2</sup> [2.6 kg/m <sup>2</sup> ]	0.53 lb/ft <sup>2</sup> [2.6 kg/m <sup>2</sup> ]
<b>TECHNICAL CHARACTERISTICS</b>				
Sport Properties	ASTM F2772	Class 1	Class 2	Class 2
Force Reduction / Cushioning	ASTM F2569	≥ 10%	≥ 22% - ≤ 27%	≥ 22% - ≤ 27%
Impact Sound Insulation	EN ISO 171-2	-	18 dB	18 dB
Fire Rating	ASTM E648	Class 1	Class 1	Class 1
<b>SUSTAINABILITY HEALTH &amp; SAFETY</b>				
Naturally Bacteriostatic: Combats MRSA, E. coli and S. aureus*	-	-	OK	OK
Allergen Free	-	-	OK	OK
Indoor Air Quality / Low Emitting Materials	EQc2 LEED v4	-	FloorScore® Certified	FloorScore® Certified
TVOC After 28 Days	ISO 16000-6	-	<100 µg/m <sup>3</sup>	<100 µg/m <sup>3</sup>
Ease of Maintenance	-	-	No Wax, No Buff for Life / PUR Protect®	No Wax, No Buff for Life / PUR Protect®
Plant Certifications	-	-	ISO 14001 and ISO 9001	ISO 14001 and ISO 9001
Restriction Use of Harmful Chemicals	Mrc4 LEED v4	-	Complies with REACH	Complies with REACH
Production Waste	-	-	100% Manufacturing Waste Recycled	100% Manufacturing Waste Recycled
Recycled Content	Mrc3 LEED v4	-	29%	29%
End of Life	-	-	100% Recyclable	
<b>INSTALLATION METHOD</b>				
Full-Spread Adhesive	ASTM F2170 (F1869)	≤ 95% RH (≤ 10lb)		
Moisture Mitigation System		≤ 92% RH (≤ 10 lb)	ISOLSPORT	
<b>WARRANTY</b>	15-year limited warranty when installed in accordance with Gerflor's installation instructions.			

\*The implementation of an effective cleaning method is the best defense against infection.