




DESCRIPTION				
Total thickness	EN ISO 24346	mm	2.00	2.00
Weight	EN ISO 23997	g/sq.m	2985	3100
Width of sheet	EN ISO 24341	cm	200	200
Length of sheet	EN ISO 24341	lm	20	20
CLASSIFICATION				
Standard / Product specification		-	EN ISO 10581	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43	34 - 43
Fire rating	EN 13501-1	class	Bfl-S1	Bfl-S1
	GB 8624	class	B1	B1
Toxic testing	GB 18586	-	OK	OK
Electrical resistance *	EN 1081	Ohm	$10^4 \leq R \leq 10^6$	$10^4 < R \leq 10^6$
Static electrical propensity	EN 1815	kV	≤ 2	≤ 2
Slip resistance	DIN EN16165 annex B	class	R9	R9
PERFORMANCE				
Type Binder content	ISO 10581	type	I	II
Dimensional stability	EN ISO 23999	%	$\leq 0,40$	$\leq 0,40$
Residual indentation (norm)	EN ISO 24343-1	Mm	$\leq 0,10$	$\leq 0,10$
Castor chair test	ISO 4918	-	OK	OK
Thermal conductivity	EN ISO 10456	W/(m.K)	0.25	0.25
Colour fastness	EN ISO 105-B02	degree	≥ 6	≥ 6
Surface treatment	-	-	Evercare	Evercare
Chemical products resistance	EN ISO 26987	-	OK	OK
Anti-bacterial activity (E. coli - S. aureus)**	ISO 22196	-	> 99 %inhibits growth	> 99 %inhibits growth
Antiviral activity (human coronavirus 229E)	ISO 21702		99.7% after 2h 99.9% after 5h	99.7% after 2h 99.9% after 5h
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	$\mu\text{g}/\text{m}^3$	< 10	< 10
Certification	-	-	Floorscore®	Floorscore®
MARQUAGE CE				
	EN 14041	-		

* Vertical resistance, measured before installation

** The implementation of an effective cleaning method is the best defence against infection