

DESCRIPTION

Total thickness	ISO 24346 (EN 428)	mm	2.0/3.0*
Weight	ISO 23997 (EN 430)	g/m ²	3800/5550*
Tile size	ISO 24342 (EN 427)	mm	608×608
Number of tiles per package		-	20/13

CLASSIFICATION

Norm / Product specification	-	-	ISO 10581 (EN 649)
European classification	ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13501-1	class	Bfl-s1
Static electrical propensity	EN 1815	KV	≤ 2
	IEC 61340-4-5	V	< 100
Electrical resistance**	EN 1081	Ω	10 ⁴ ≤ VR ≤ 10 ⁶
Slip resistance wet	DIN EN 16165	class	R9






PERFORMANCES

Type binder content	ISO 10581	type	II
Dimensional stability	ISO 23999 (EN 434)	%	0.25
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness	ISO 105 - B02	degree	≥ 6
Chemical products resistance	ISO 26987 (EN 423)	-	OK
Color number	-	-	6

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000 - 6	µg/m ³	< 10
--------------------	---------------	-------------------	------

CE MARKING

	EN 14041	   
---	----------	---

** Measured before installation

*Support 3mm type

TECHNIC EL5 MOQ:177sqm (24boxes)

2mm: 20 pcs/box

3mm :13 pcs/box