

| DESCRIPTION | | | ULTRA | ULTRA H2O | STANDARD | H2O | SUPER |
|------------------------|--------------|------------------|--------|-----------|----------|--------|--------|
| Total thickness | EN ISO 24346 | mm | 2.0 | 2.0 | 2.0 | 2.0 | 2.20 |
| Thickness of wearlayer | EN ISO 24340 | mm | 1.16 | 1.0 | 0.85 | 0.85 | 1.12 |
| Weight | EN ISO 23997 | g/m ² | 2460 | 2460 | 2460 | 2350 | 2880 |
| Width/length of sheet | EN ISO 24341 | cm/lm | 200/20 | 200/20 | 200/20 | 200/20 | 200/20 |

| CLASSIFICATION | | | ULTRA | ULTRA H2O | STANDARD | H2O | SUPER |
|-----------------------------------|---------------------------|---------------|------------|------------|------------|------------|------------|
| European classification | EN ISO 10874 | class | 34-43 | 34-43 | 34-43 | 34-43 | 34-43 |
| Fire rating | AS ISO 9239-1 | kW/m2 smoke % | 8.3 134 | 8.5 112 | 8.4 199 | 8.9 132 | 8.7 167 |
| Static Electrical Propensity | EN 1815 | kV | <2 | <2 | <2 | <2 | <2 |
| Slip Resistance wet pendulum | AS 4586 2013 (Appendix A) | class | P4 | P3 | P4 | P5 | P5 |
| Slip resistance oil-wet ramp | AS 4586 2013 (Appendix D) | class | R10 | R11 | R10 | R11 | R12 |
| Slip resistance wet/barefoot ramp | AS 4586 2013 (Appendix C) | class | - | C | - | B | - |
| Surface roughness | - | µm | Rz≥20 | Rz≥20 | Rz≥20 | Rz≥20 | Rz≥20 |

| PERFORMANCE | | | ULTRA | ULTRA H2O | STANDARD | H2O | SUPER |
|---------------------------------|--------------|-----------------|-------------------------------|-------------------------------|------------------------|------------------------|-------------------------------|
| Abrasion resistance | EN 660.2 | mm ³ | ≤2 | ≤4 | ≤2 | ≤2 | ≤2 |
| Abrasion group | - | group | T | P | T | T | T |
| Dimensional stability | EN ISO 23999 | % | ≤0.40 | ≤0.40 | ≤0.40 | ≤0.40 | ≤0.40 |
| Castor chair test (Type W) | ISO 4918 | - | Good | Good | Good | Good | Good |
| Residual indentation | EN ISO | mm | ≤0.03 | ≤0.10 | ≤0.05 | ≤0.10 | ≤0.10 |
| Thermal conductivity | EN ISO 10456 | W/(m.K) | 0.25 | 0.25 | 0.25 | 0.25 | 0.25 |
| Colour fastness | EN 20 | degree | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 |
| Chemical products fastness | EN ISO 26987 | - | Good | Good | Good | Good | Good |
| Surface treatment | - | - | SparClean ⁺ | - | PUR | SparClean ⁺ | - |
| Anti-bacterial activity MRSA(2) | ISO 22196 | - | >99% inhibits bacteria growth | >99% inhibits bacteria growth | >99% inhibits bacteria | >99% inhibits bacteria | >99% inhibits bacteria growth |

| ENVIRONMENT | | | ULTRA | ULTRA H2O | STANDARD | H2O | SUPER |
|-----------------|---|------------------------------|-----------|-----------|-----------|-------|-----------|
| TVOC | - | mg/m ² /hr (24hr) | 0.188 | 0.266 | 0.215 | < 100 | 0.266 |
| Global GreenTag | - | - | GreenRate | GreenRate | GreenRate | - | GreenRate |

INSTALLATION should be carried out in accordance with local standards. The subfloor should be smooth, hard, clean, dry and free from contamination prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatise for 24 hours before installation, in a room temperature of between 18-24°C where the product will be installed.

MAINTENANCE should be carried out regularly to retain the appearance and durability of the floor. The floorcoverings should be maintained with regular sweeping and damp mopping. A more intense cleaning regime should be carried out periodically with a machine using a red pad and a neutral cleaner. No seals, polishes or waxes should be applied to the floorcovering, as this will impair the slip resistance of the floor.

ADHESIVES: Please refer to Gerflor installation guidelines on gerflor.com.au

IMPORTANT: Gerflor has a policy of continuous product and product data improvement. It reserves the right to change design and specifications without notice. The information contained in this document is valid from 01/01/2024 and is subject to change at any time without notice. In the context of constantly changing technology our customers are responsible, prior to any use, for checking with us that this document is the version in force.

To download the full Tarasafe range installation instructions, maintenance guides and certifications visit www.gerflor.com.au

Manufactured using recycled card.
A sampling service is available for your convenience - 1800 060 785
GERFLOR AUSTRALASIA PTY LTD
Tel +613 98321333
Email: custorders@gerflor.com.au



We care / we act Our commitments for a sustainable future




CARBON FOOTPRINT[†]
-20 % kg CO₂ equivalent/m² between 2020 and 2025


BIOSOURCED CONTENT^{}**
10 % by 2025


RECYCLED CONTENT
30 % by 2025


ADHESIVE FREE^{*}**
35 % by 2025


ANNUAL VOLUME RECYCLED
60 000 t by 2025

[†] Scopes 1 and 2 defined in the GHG protocol ^{**} % of activity with biosourced materials ^{***} % of activity - adhesive free solution