

DESCRIPTION

EPDM and natural vulcanized rubber

Properties	Standard	Unity	Value
Thickness	NF EN ISO 24346	mm	6
Weight	NF EN ISO 23997	Kg/m ²	7
Size	NF EN ISO 24342	mm	1021 x 1021
CLASSIFICATION			
Fire resistance	AS/ISO 9239.1-2003	kW/m ² Smoke %/min	3.9 248
Slip resistance wet pendulum	AS4586:2013 Appendix A	class	P3
Slip resistance oil wet ramp	AS4586:2013 Appendix D	class	R10
PERFORMANCE			
Dimensional stability	NF EN ISO 23999	%	<0,1
Curling	NF EN ISO 23999	mm	0
Abrasion	EN ISO 5470-1	g	<1
Light resistance	EN ISO 20105 - A02	degree	3
Indentation resistance 50kgs/5cm ²	EN 1516	mm	0.02
Slip resistance in dry condition	EN 13036-4	unit	87
Tensile strength	EN ISO 1798	MPa	2,5
Elongation at break	EN ISO 1798	%	220
Hardness shore A	Int.	-	68
Shock absorption	EN14808	%	10
Static load	-	-	17.5kg/cm ²
TVOC	ASTM D5116	<0.19/m ² .hr	Pass