

 Gerflor the flooring group	Mipolam Planet R10		
DESCRIPTION			
Total thickness	EN ISO 24346	mm	2.00
Weight	EN ISO 23997	g/sq.m	2700
Width of sheet	EN ISO 24341	cm	200
Length of sheet	EN ISO 24341	lm	20
CLASSIFICATION			
Norm / Product specification	-	-	EN ISO 10581
European classification	EN ISO 10874	class	34 - 43
Fire rating	EN 13 501-1	class	B _{fl} -s ¹
Static electrical propensity	EN 1815	kV	≤2
PERFORMANCE			
Type Binder content	EN ISO 10581	type	I
Dimensional stability (requirement)	EN ISO 23999	%	≤ 0.40
Residual indentation (norm)	EN ISO 24343-1	mm	≤ 0.10
Slip resistance	DIN EN 16165 annex B (DIN 51130)	Class	R10
Castor chair test	ISO 4918	-	OK
Colour fastness	EN ISO 105-B02	degree	≥ 7
Surface treatment	-	-	Evercare™
Chemical products resistance	EN ISO 26987	class	OK
Anti-bacterial activity (E.coli – S. aureus) *	ISO 22196	-	> 99 % inhibits growth
Antiviral activity (human coronavirus 229E)	ISO 21702		99.7% after 2h 99.9% after 5h
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
Certification	-	-	Floorscore®
CE MARKING			
	EN 14041	-	

* The implementation of an effective cleaning method is the best defence against infection