




		PREMIUM COMFORT 特优舒适	
DESCRIPTION 规格		Osmoz – Indiana – Metallica – Brazilia – Poesy - Neopolis	
Total thickness 总厚度	EN ISO 24346	mm	3.00-3.30
Thickness of the wearlayer 耐磨层厚度	EN ISO 24340	mm	1.02 – 1.17
Weight 重量	EN ISO 23997	g/sq.m	2800-3260
Width of sheet 卷宽	EN ISO 24341	cm	200
Length of sheet 卷长	EN ISO 24341	lm	25
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	EN ISO 11638(EN651)
European classification 产品分级	EN ISO 10874	class	34 -42
Fire rating 防火等级	EN 13 501-1	class	Bfl-s1
	GB 8624-2012	class	B ₁
Static electrical propensity 抗静电性	EN 1815	kV	≤2
Slip resistance 防滑性 (1)	DIN EN 16165 annex B (DIN 51130)	class	R10
PERFORMANCES 性能			
Wear resistance 耐磨性	EN 660-2	mm ³	≤2.0
Wear group 耐磨等级	-	group	T
Dimensional stability 尺寸稳定性	EN ISO 23999	%	≤ 0.40
Residual indentation (requirement) 残余凹陷度	EN ISO 24343-1	mm	≤ 0.20
Impact sound insulation 隔音(隔声)性能	En ISO 717-2	dB	17 (Osmoz – Indiana– Brazilia – Poesy – Neopolis) 16 (Metallica)
Castor chair test 椅子脚轮测试	ISO 4918	-	OK
Thermal conductivity 热传导性	EN ISO 10456	W/(m.K)	0.25
Colour fastness 色牢度	EN ISO 105-B02	degree	≥ 6
Surface treatment 特殊维护处理	-	-	Evercare™
Chemical products resistance 抗化学性	EN ISO 26987	-	OK
Anti-bacterial activity 抑菌性能 (E. coli - S. aureus 大肠杆菌和金黄色葡萄球菌) (2)	ISO 22196	-	> 99 % 抑菌率
Anti-Viral activity (human coronavirus 229E) 抗病毒活性 (人类冠状病毒229E) (2)	ISO 21702	-	2小时后> 99.7%
ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量			
Certification 证书	-	-	Floorscore®
	GB 18586-2001		OK
CE MARKING 标识			
	EN 14041	 防滑  供地下暖气设备使用  抗静电  防火	

(1) For lifetime sustainable wet resistance, please refer to Tarasafe ranges. 想获得终身持续的防湿滑性能，请参考Tarasafe系列。

(2) The implementation of an effective cleaning regime is the most important defence against infection. 实施有效的清洁方法是抗感染最重要的防御措施。