

DESCRIPTION 规格

Total thickness on grain side 总厚度	EN ISO 24346	mm	2.00
Wear layer thickness 耐磨层厚度	EN ISO 24340	mm	0.85
Weight 重量	EN ISO 23997	g/m ²	2350
Width of sheet 卷宽	EN ISO 24341	cm	200
Length of sheet 卷长	EN ISO 24341	lm	20

CLASSIFICATION 类别

Norm / Product specification 产品规范	-	-	EN ISO 10582
European classification 产品分级	EN ISO 10874	class	34 - 43
Fire rating 防火等级	EN 13501-1	class	B _{fl} -s1
	GB 8624-2012	class	B1
Static electrical propensity 抗静电性	EN 1815	kV	≤2
Slip resistance wet: ramp test with oil 防湿滑性: 斜坡油	DIN EN 16165 annex B (DIN 51130)	class	R11
Slip resistance wet : bare foot 防湿滑性: 赤足	DIN EN 16165 annex A (DIN 51097)	class	B
Slip resistance - ramp test 防滑 - 斜坡	EN 13845-C	class	Esf-Esb






PERFORMANCE 性能

Type Binder content 粘合物分级	EN ISO 10582	type	I
Dimensional stability 尺寸稳定性	EN ISO 23999	%	≤ 0.40
Residual indentation 残余凹陷度	EN ISO 24343-1	mm	≤ 0.10
Castor chair test 椅子脚轮测试	ISO 4918	-	OK
Thermal conductivity 热传导性	EN ISO 10456	W/(m.K)	0.25
Colour fastness 颜色稳定性	EN ISO 105-B02	degree	≥6
Chemical products resistance 抗化学性	EN ISO 26987	-	OK

ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量

TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/ m ³	< 100
Certification 证书	-	-	Floorscore®
	GB 18586-2001	-	OK

CE MARKING 标识

	EN 14041	-	 防滑  供地下暖气设备使用  抗静电  防火
---	----------	---	--