

**DESCRIPTION**

Total thickness	EN ISO 24346 (EN 428)	mm	2.20
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	1.12
Weight	EN ISO 23997 (EN 430)	g/m <sup>2</sup>	2880
Width of sheet	EN ISO24341 (EN 426)	cm	200
Length of sheet	EN ISO24341 (EN 426)	ml	20

**CLASSIFICATION**

Norm / Product specification	-	-	EN ISO 10582 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	34 - 43
Fire rating	EN 13 501-1	class	B <sub>fl</sub> -s1
Static electrical propensity	EN 1815	kV	≤2
Slip resistance wet : ramp test with oil	DIN EN 16165 annex B (DIN 51130)	class	R12






**PERFORMANCES**

Wear resistance	EN 660-2	mm <sup>3</sup>	≤ 2
Wear group	EN 649	group	T
Type binder content	EN ISO 10582	type	I
Dimensional stability	EN ISO 23999 (EN 434)	%	≤ 0.40
Residual indentation (requirement)	EN ISO 24343-1 (EN 433)	mm	≤ 0.10
Castor chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal conductivity	EN ISO 10456 (EN 12 524)	W/(m.K)	0.25
Colour fastness	EN ISO 105-B02	degree	≥ 6
Chemical products resistance	EN ISO 26987 (EN 423)	-	OK
Anti-bacterial activity (MRSA) (1)	ISO 22196	-	> 99% Inhibits growth

**ENVIRONMENT / INDOOR AIR QUALITY**

Certification	-	-	Floorscore®
---------------	---	---	-------------

**CE MARKING**

	EN 14041	-	  
		-	

(1) The implementation of an effective cleaning regime is the best defence against infection