


DESCRIPTION 规格		TREND				
Total Thickness 总厚度	EN ISO 24346	mm	2			
Thickness of the wearlayer 耐磨层厚度	EN ISO 24340	mm	0,40			
Weight 重量	EN ISO 23997	g/m ²	3180			
Size 尺寸	EN ISO 24342	mm	457,2 x 914,4	609,6 x 609,6	184,15 x 1219,2	230,0 x 1500,0
Number of planks /tiles and sqm per box 片状数量及平米数/每箱	-	-	11 / 4,60 m ²	13 / 4,83 m ²	21 / 4,71 m ²	13 / 4,49 m ²
CLASSIFICATION 类别						
Norm/Product Specification 产品规范	-	-	EN ISO 10582			
European Classification 产品分级	EN ISO 10874	class	23 - 32 - 41			
Fire Rating 防火等级	EN 13 501-1	class	Bfl-s1			
	GB 8624-2012	class	B ₁ (B-s ₁ ,t0)			
Toxic testing 有毒有害物质检测	GB 18586 - 2001	-	PASS			
Static Electrical Propensity 抗静电性	EN 1815	kV	≤2			
Slip Resistance Wet 防湿滑性	DIN EN 16165 annex B(DIN 51130)	class	R10			
PERFORMANCES 性能						
Wear Resistance 耐磨性	EN 660-2	mm ³	≤2.0			
Wear Group 耐磨等级	-	group	T			
Type Binder content 粘合物等级	ISO 10582	group	I			
Dimensional stability (norm) 尺寸稳定性	EN ISO 23999	%	≤ 0,25			
Residual Indentation 残余凹陷	EN ISO 24343-1	mm	≤ 0,10			
Castor chair test 椅子脚轮测试	ISO 4918	-	OK			
Thermal Conductivity 热传导性	EN ISO 10456	W/(m.K)	0,25			
Colour Fastness 颜色稳定性	EN ISO 105-B02	degree	≥ 6			
Surface Treatment 特殊维护处理	-	-	Protecshield™			
Chemical Products Resistance 抗化学品性	EN ISO 26987		OK			
ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量						
TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/ m ³	< 10			
CE MARKING CE标志						
	EN 14041		