

DESCRIPTION 规格		CREATION 70 DESIGN										CREATION 70	
Total Thickness 总厚度	EN ISO 24346	mm	2,50										2,50
Thickness of the wearlayer 耐磨层厚度	EN ISO 24340	mm	0,70										0,70
Weight 重量	EN ISO 23997	g/m ²	4100										3960
Size 尺寸	EN ISO 24342	mm	184x1219 chevron	184x1219	230x1500	76/152/228 X914 Mix planks	610x610	914x914	457x914	228x914	152/305/457 X914 Mix tiles	208x1243	
Number of planks / tiles and sqm per box 片状数量及平米数/每箱	-	-	14 / 3.14 m ² chevron	15 / 3.36 m ²	9 / 3.11 m ²	8+8+8 / 3.34 m ² Mix planks	9 / 3.35 m ²	5 / 4.18 m ²	9 / 3.76 m ²	17 / 3.54 m ²	4+4+4 3.34 m ² Mix tiles	14 / 3.62 m ²	
CLASSIFICATION 类别													
Norm/Product Specification 产品规范	-	-	EN ISO 10582										
European Classification 产品分级	EN ISO 10874	class	34 - 43										
Fire Rating 防火等级	EN 13 501-1	class	Bfl-s1										
	GB 8624-2012	class	B ₁ (B-s ₁ ,t0)										
Toxic testing 有毒有害物质检测	GB 18586 - 2001	-	Pass										
Static Electrical Propensity 抗静电性	EN 1815	kV	≤2										
Slip Resistance Wet 防湿滑性	DIN EN 16165 annex B(DIN 51130)	class	R10										
PERFORMANCES 性能													
Wear Resistance 耐磨性	EN 660-2	mm ³	≤2										
Wear Group 耐磨等级	-	group	T										
Type Binder content 粘合物等级	ISO 10582	type	I										
Dimensional stability (norm) 尺寸稳定性	EN ISO 23999	%	≤ 0.25										
Residual Indentation 残余凹陷	EN ISO 24343-1	mm	≤ 0.10										
Castor chair test 椅子脚轮测试	ISO 4918	-	OK										
Thermal Conductivity 热传导性	EN ISO 10456	W/(m.K)	0,25										
Colour Fastness 颜色稳定性	EN ISO 105-B02	degre	≥ 6										
Surface Treatment 特殊维护处理	-	-	PUR+Matt										
Chemical Products Resistance 抗化学品性	EN ISO 26987	-	OK										
ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量													
TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/ m3	< 10										
Certification 认证	-	-	Floorscore®										
CE MARKING CE标志													
CE	EN 14041												