

DESCRIPTION 规格			
Total thickness 总厚度	EN ISO 24346 [EN 428]	mm	4,60
Thickness of wearlayer 耐磨层厚度	EN ISO 24340 (EN 429)	mm	0,70
Weight 重量	EN ISO 23997 [EN 430]	g/m ²	5595
Tile size 尺寸	ISO 24342 [EN 427]	mm	500 x 500
Number of tiles per package 片状数量/每箱	-	-	10
Coverage / box 平米数/每箱	-	sq.m	2,5
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	EN 652
European classification 产品分级	EN ISO 10874 (EN 685)	class	34 - 42
Fire rating 防火等级	EN 13 501-1	class	B _{fl} -s1
Toxic testing 有毒有害物质检测	GB 18586 - 2001	-	PASS
Static electrical propensity 抗静电性	EN 1815	kV	≤2
Slip resistance wet :ramp test with oil 防湿滑性	DIN EN 16165 annex B(DIN 511	class	R10
PERFORMANCE 性能			
Wear resistance 耐磨性	EN 660-2	mm ³	≤2.0
Wear group 耐磨等级	EN 652	group	T
Dimensional stability 尺寸稳定性	EN ISO 23999 [EN 434]	%	≤0.25
Residual indentation 残余库存	EN ISO 24343-1 [EN 433]	mm	≤0.4
Castor chair test 椅子脚轮测试	ISO 4918 (EN 425)	-	OK
Impact sound insulation 隔音 (隔声) 性能	EN ISO 717-2	dB	15
Thermal conductivity 热传导性	EN ISO 10456 (EN12524)	W/(m.K)	0,25
Colour fastness 颜色稳定性	EN ISO 105-B02	degree	≥ 6
Surface treatment 特殊维护处理	-	-	Protecsol®
Chemical products resistance 抗化学品性	EN ISO 26987 [EN 423]	-	OK
ENVIRONMENT / INDOOR AIR QUALITY 环保/室内空气质量			
TVOC after 28 days 28天后TVOC排放量	ISO 16000-6	µg/ m ³	< 10
Certification 证书	-	-	Floorscore®
CE MARKING CE标志			
	EN 14041	-	
		-	