


<b>DESCRIPTION</b>			
Total thickness	EN ISO 24346 [EN 428]	mm	4,60
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	0,70
Weight	EN ISO 23997 [EN 430]	g/m <sup>2</sup>	5595
Tile size	ISO 24342 [EN 427]	mm	500 x 500
Number of tiles per package	-	-	10
Coverage / box	-	sq.m	2,5
<b>CLASSIFICATION</b>			
Norm / Product specification	-	-	EN 652
European classification	EN ISO 10874 (EN 685)	class	34 - 42
Fire rating	EN 13 501-1	class	B <sub>fl</sub> -s1
Static electrical propensity	EN 1815	kV	≤2
Slip resistance wet :ramp test with oil	DIN EN 16165 annex B(DIN 511	class	R10
<b>PERFORMANCE</b>			
Wear resistance	EN 660-2	mm <sup>3</sup>	≤2.0
Wear group	EN 652	group	T
Dimensional stability	EN ISO 23999 [EN 434]	%	≤0,25
Residual indentation	EN ISO 24343-1 [EN 433]	mm	≤0.4
Castor chair test	ISO 4918 (EN 425)	-	OK
Impact sound insulation	EN ISO 717-2	dB	15
Thermal conductivity	EN ISO 10456 (EN12524)	W/(m.K)	0,25
Colour fastness	EN ISO 105-B02	degree	≥ 6
Surface treatment	-	-	Protecsol®
Chemical products resistance	EN ISO 26987 [EN 423]	-	OK
<b>ENVIRONMENT / INDOOR AIR QUALITY</b>			
TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10
Certification	-	-	Floorscore®
<b>CE MARKING CE</b>			
<b>CE</b>	EN 14041	-	
		-	