

DESCRIPTION		TREND	DESIGN
Total Thickness	EN ISO 24346	mm	2,50
Thickness of the wearlayer	EN ISO 24340	mm	0,55
Weight	EN ISO 23997	g/m ²	3'850
Size	EN ISO 24342	mm	4'410
Number of planks/tiles and sqm per box		457 mm x 914 mm – 9 tiles / 3,76m ² 610 mm x 610 mm – 9 tiles / 3,35m ² 184 mm x 1219 mm – 15 planks / 3,36m ² 152 mm x 762 mm – 33 planks / 3,82m ² 230 mm x 1500 mm – 9 planks / 3,11m ² 914 mm x 914 mm – 5 planks / 4,18 m ²	
CLASSIFICATION			
Norm/Product Specification	-	-	EN ISO 10582
European Classification	EN ISO 10874	class	33 - 42
Fire Rating	EN 13 501-1	class	B _{fl} -s1
Static Electrical Propensity	EN 1815	kV	≤2
Slip Resistance Wet	DIN EN 16165 annex B(DIN 51130)	class	R10
PERFORMANCES			
Wear Resistance	EN 660-2	mm ³	≤2.0
Wear Group	-	group	T
Type Binder content	ISO 10582	group	I
Dimensional stability (norm)	EN ISO 23999	%	≤ 0,25
Residual Indentation	EN ISO 24343-1	mm	≤ 0,10
Castor chair test	ISO 4918	-	OK
Thermal Conductivity	EN ISO 10456	W/(m.K)	0,25
Colour Fastness	EN ISO 105-B02	degree	≥ 6
Surface Treatment	-	-	ProtecShield™
Chemical Products Resistance	EN ISO 26987		OK
ENVIRONMENT / INDOOR AIR QUALITY			
TVOC after 28 days	ISO 16000-6	µg/ m ³	< 10
CE MARKING			
CE	EN 14041		