


DESCRIPTION		CREATION 70 DESIGN										CREATION 70
Total Thickness	EN ISO 24346	mm	2,50									2,50
Thickness of the wearlayer	EN ISO 24340	mm	0,70									0,70
Weight	EN ISO 23997	g/m ²	4100									3960
Size	EN ISO 24342	mm	184x1219 chevron	184x1219	230x1500	76/152/228 X914 Mix planks	610x610	914x914	457x914	228x914	152/305/457 X914 Mix tiles	208x1243
Number of planks / tiles and sqm per box	-	-	14 / 3.14 m ² chevron	15 / 3.36 m ²	9 / 3.11 m ²	8+8+8 / 3.34 m ² Mix planks	9 / 3.35 m ²	5 / 4.18 m ²	9 / 3.76 m ²	17 / 3.54 m ²	4+4+4 3.34 m ² Mix tiles	14 / 3.62 m ²
CLASSIFICATION												
Norm/Product Specification	-	-	EN ISO 10582									
European Classification	EN ISO 10874	class	34 - 43									
Fire Rating	EN 13 501-1	class	Bfl-s1									
	GB 8624-2012	class	B ₁ (B-s ₁ ,t0)									
Toxic testing	GB 18586 - 2001	-	Pass									
Static Electrical Propensity	EN 1815	kV	≤2									
Slip Resistance Wet	DIN EN 16165 annex B	class	R10									
PERFORMANCES												
Wear Resistance	EN 660-2	mm ³	≤2									
Wear Group	-	group	T									
Type Binder content	ISO 10582	type	I									
Dimensional stability (norm)	EN ISO 23999	%	≤ 0.25									
Residual Indentation	EN ISO 24343-1	mm	≤ 0.10									
Castor chair test	ISO 4918	-	OK									
Thermal Conductivity	EN ISO 10456	W/(m.K)	0,25									
Colour Fastness	EN ISO 105-B02	degree	≥ 6									
Surface Treatment	-	-	PUR+Matt									
Chemical Products Resistance	EN ISO 26987		OK									
ENVIRONMENT / INDOOR AIR QUALITY												
TVOC after 28 days	ISO 16000-6	µg/ m3	< 10									
Certification	-	-	Floorscore®									
CE MARKING												
	EN 14041		