



TARAFLEX® SPORT M COMFORT

MAXIMUM CUSHION, SAFETY AND INJURY PREVENTION

The first Taraflex® sports floor in ASTM F2772 C4 category. Gerflor's technology and innovation knowledge bring superior cushioning, comfort and safety during the practice of physical activities.

- ▶ Perfect for sports training camps
- ▶ ASTM F2772 Class 4: $\geq 46\%$ - $< 57\%$ shock absorption
- ▶ Ball bounce: $\geq 96\%$
- ▶ Impact Protection Index (IPI): 88%
- ▶ Most cushioning to prevent short term and overuse injuries
- ▶ Triple density foam




3764 Taupe	6758 Silver Gray	6873 Anthracite	6211 Gold	6146 Coral
6038 Terracotta	6159 Pink	6180 Red	6559 Spring	6570 Mint Green
6557 Forest	2404 London Light Blue	6445 Lagoon	6431 Teal	6430 Blue
6830 Black	0012 Navy Blue	6457 Blueberry	7755 Pure Concrete	4537 Basketball Pattern
7422 Blue Wave	5763 Maple	6375 Oak	6350 Light Cherry	6391 Wood Grey
7019 Wood Crosscut	7020 Golden Herringbone	4536 Wood Dark Blue	6390 Wood Red	4535 Wood Forest Green

TARAFLEX® SPORT M COMFORT

MAXIMUM COMFORT, SAFETY AND INJURY PREVENTION

COMFORT D-Max™ DURABILITY
 TRIPLE ACTION
Protēcsol

DESCRIPTION	STANDARDS	REQUIREMENTS	WOOD DESIGNS	SOLID COLORS
PRODUCT DESCRIPTION				
Wearlayer	-	-	100% Pure Vinyl	
Surface Complex	-	-	D-Max™	
Foam Backing	-	-	Triple Density CXP HD	
Total Thickness	-	-	0.47" (12.5 mm)	
Wearlayer Thickness	-	-	0.08" (2.1 mm)	
Weight	-	-	1 lb/ft² (5.1 kg/m²)	
Roll Width	-	-	4' 11" (1.5 m)	
Roll Length	-	-	86'6" (26.4 m)	
SPORT PROPERTIES				
Sport Properties	ASTM F2772	-	Class 4	
Safety	ASTM F2772	≥ 10%	≥ 46% - < 57%	
Vertical Deformation	ASTM F2772	≤ 0.138" (≤ 3.5 mm)	≤ 0.138" (≤ 3.5 mm)	
Sliding Effect	ASTM F2772	80 - 110	80 - 110	
Ball Rebound	ASTM F2772	≥ 96%	≥ 96%	
Impact Protection Index (IPI)	IPI	-	88%	
Anti-Friction Burns	-	-	Protēcsol	
TECHNICAL CHARACTERISTICS				
Chemical Product Resistance	ASTM D543	-	Excellent	
Resistance to a Rolling Load	EN 1569	≥ 1500 N	≥ 1500 N	
Fire Rating	ASTM E648	Class 1	Class 1	
ENVIRONMENT HEALTH & SAFETY				
Ease of Maintenance	-	-	Protēcsol / No wax for life	
Restriction Use of Harmful Chemicals	MRC4 LEED v4	-	Complies with REACH	
Antimicrobial Treatment	ISO 22196	-	Inhibits spread of bacteria at 99.9%	
Allergen Free	-	-	OK	
Indoor Air Quality	EQc2 LEED v4	-	Floorscore™	
Recycled Content	MRC3 LEED v4	-	22%	
INSTALLATION METHOD				
Full-Spread Adhesive	ASTM F2170 (F1869)	≤ 90% RH (≤ 10 lb)		
Eco-Fit™ System	-	-	-	
WARRANTY	15-year limited manufacturer warranty when installed in accordance with Gerflor's installation instructions			