

	<b>MIPOLAM® BIOCONTROL PURE 美宝琳® BIOCONTROL PURE</b>		
	<b>PRODUCT CHARACTERISTICS 产品特性</b>		
	<b>Standard 标准</b>	<b>Unit 单位</b>	<b>Results 结果</b>
	<b>PRODUCT DESCRIPTION 产品描述</b>		
Thickness 厚度	ISO 24346 (EN 428)	mm	2
Length of sheet 卷长	ISO 24341 (EN 426)	lm	20
Width of sheet 卷宽	ISO 24341 (EN 426)	m	2
	<b>CLASSIFICATION 类别</b>		
Norm / Product specification 产品规范	-	-	ISO 10581(EN 649)
Type binder content 粘合剂分级	ISO 10581	type	I
European classification 产品分级	ISO 10874 (EN 685)	class	34 - 43
Fire rating 防火等级	EN 13 501-1	class	Bfl-s1
	GB 8624 - 2012	-	B1(B-s1,t0)
Toxic testing 有毒有害物质检测	GB 18586-2001	-	合格
Static electrical propensity 抗静电性	EN 1815	KV	≤ 2
Thermal conductivity 热传导性	ISO 10456 (EN 12524)	W/(m.K)	0.25
Slip resistance dry 防干滑性	EN 13893	-	≥ 0.3
Slip resistance wet 防湿滑性	DIN EN 16165	class	R9
	<b>CLEANROOM CHARACTERISTICS 洁净室特性</b>		
Particulate Emission 颗粒排放	ISO 14644-1	class	ISO 1
Particulate Cleanability 颗粒清洁	VDI 2083 Part 17	-	优秀 - 清洁后无残留颗粒
Outgassing VOC/SVOC 释放气体 VOC/SVOC	ISO 14644-8	g/m <sup>3</sup> *s	未检出
Outgassing Ammonia 释放气体 氨	ISO 14644-8	g/m <sup>3</sup> *s	未检出
Outgassing Inorganic acids 释放气体 无机酸	ISO 14644-8	g/m <sup>3</sup> *s	未检出
Outgassing organic compound* 释放气体 有机化合物	ISO 14644-8	g/m <sup>3</sup> *s	未检出
Chemical resistance 24 Hours (including H2O2) 抗化学性24小时 (含H2O2)	ISO 2812-1	-	优秀
	VDI 2083 Part 17	-	优秀
H2O2 Absorption / Desorption H2O2 吸收 / 释放	VDI 2083 Part 20	-	快速释放 (良好)
Resistance on Microorganism development on the floor 地板抗微生物生长	ISO 846	Procedure A (fungi 霉菌)	良好
		Procedure C (bacterial 细菌)	良好
	<b>DECLARATION OF PERFORMANCE 认证</b>		
	EN14041		

\* Including Amines, Organophosphates, Siloxanes and Phthalates. 包括胺类, 有机磷酸酯类, 硅氧烷类, 邻苯二甲酸酯类。