

TARAFLEX SURFACE is a 2 mm sport flooring, heterogeneous calendered roll, embossed, available in 1,5 m wide sheet and with a length up to 26,5 m.

The product comprises a UV cured polyurethane surface treatment PROTECSOL®, ensuring easy maintenance and the right balance between slide and grip and a D MAX surface complex. It is composed of inlaid colours or of printed designs encapsulated by a transparent wear layer.

The vertical deformation following EN 14809 is  $\leq 2,0$  mm and the slippery resistance following EN 13036-4 stays between 80 and 110. Abrasion resistance following EN 1517 is  $\leq 350$  mg. This product allows a 3 dB sound insulation. Its construction allows him a ball rebound  $\geq 101\%$ .

The product consists of up to 88% biocontent, mineral and recycled content, including up to 18% of biocontent.

According to ISO 21702, TARAFLEX SURFACE shows anti-viral activity against Human Coronaviruses : it reduces the number of virus by 99,37% after 2h00. According to ISO 22196, it has anti-bacterial activity against E. coli, S. aureus and MRSA of 99% after 24h00. This product allows a Bfl-s1 fire rating.

It does not contain any heavy metals or CMR 1&2 components, it is 100% compliant with REACH. The product emission rate of volatile organic compounds is  $<100\mu\text{g}/\text{m}^3$  (TVOC after 28 days ISO 16000-6). It is 100% recyclable.

Based on the EPD, The Global Warming Potential of this product is 10,6 kg CO<sub>2</sub> eq./m<sup>2</sup> for a use of 25 years for a customer based in Europe (end of life : 100% landfill).

Manufacturer shall provide upon request full EN14904 test report carried out by independent and approved test laboratory, and a declaration of performance for this product.

This product is certified by the federations AVC, IHF, EHF, IFF (on a wooden subfloor).

---